

# KANTILAL CHIMANLAL

AHMEDABAD  
SINCE-1913

## CAST IRON DOUBLE POST SAFETY VALVE

### SPECIFICATIONS

'SANT' Cast Iron Double Post Safety Valve  
High Lift  
Spring Loaded  
Monel Seats  
Stainless Steel Spindle  
Inlet Flanged to BS:10 Table F  
Outlets Flanged to BS:10 Table D  
Maximum BOP = 150 Psig

### TESTING & CERTIFICATION

All valves are hydraulically tested to 300 Psig  
All valves are set at 150 Psig. Saturated steam at our works before despatch.

Valves can also be set at any set pressure below 150 Psig on request

Test Certificate in Form IIIC as per IBR is furnished with every supply.

### MATERIALS


Components	Material	Material Specification
Body, Spring Chamber, Cover, Spring Discs, Cap & Easing Lever	Cast Iron	IS:210 Gr.FG200
Body Seat Ring, Valve Disc	Monel Metal	Ni Cu Alloy
Bushes, Cotter, Adjusting Screw, Regulating Ring with Ring & Screw	Bronze	IBR 282(a)(iv) Gr.B
Gasket	Compressed Asbestos Fibre	IS:2712 Gr.C
Spring	Spring Steel	IBR 307 to 314
Fasteners	Mild Steel	IS:226

### DIMENSIONS

Nominal Size	A	B	C	F	T	H
1	1½	1½	6	5½	5/8	486
1½	2½	2½	6½	7¼	7/8	570
2	3	3	7½	8	7/8	585
	(inch)	(inch)	(inch)	(inch)	(inch)	(mm)

SANT

CI 9



### Application

Water	Oil	Gas	Steam
			●

KANTILAL CHIMANLAL  
662/45, Kapasia Bazaar  
Railwayपुरa, Ahmedabad-3800 02  
Gujarat (INDIA)

Ph.: +91 79 2217 0041 / 80  
Fax: +91 79 2212 1863  
Mobile: +91 98795 15172  
E-mail : kc@kantilalchimanlal.net

' For Guaranteed Trouble Free Service '